

**Sandwich elements for the building of walls or roofs**

Patent Number: EP0967343  
Publication date: 1999-12-29  
Inventor(s): BUCH HANS-JUERGEN (DE); CLEMENS HEINZ-WILLI (DE); FRANZ PETER W (DE); REUTER MANFRED (DE); SYDOW JOCHEN (DE)  
Applicant(s):: THYSSEN KRUPP STAHL AG (DE)  
Requested Patent: ☐ EP0967343, A3  
Application Number: EP19990108847 19990504  
Priority Number (s): DE19981024597 19980602  
IPC Classification: E04B7/22 ; E04D3/35 ; E04C2/292  
EC Classification: E04B7/20A, E04C2/292, E04D3/35  
Equivalents: CZ9901948, ☐ DE19824597, HR990155, PL333167, SK72499

**Abstract**

A lightweight, thermally insulated building panel has a rigid foam inner block (2) sandwiched between an outer corrugated steel shell (4) and an inner flat steel shell (5). The outer edges of the panels have sealing profiles which interlock between adjoining panels to form a weatherproof seal. The joint has three sealing faces and has integral drainage channels which duct away moisture e.g. when used for roofing. The corrugations are formed by alternate radii linked by common tangents (13).

Data supplied from the esp@cenet database - I2